


## Thermo Scientific Fiberlite F23-48x1.5 Rotor

F23-48x1.5



## ROTOR SPECIFICATIONS

<b>Type</b>	Fixed Angle	
<b>Material</b>	Carbon Fiber Composite	
<b>Capacity</b>	48 x 1.5 mL	
<b>Maximum Speed</b>	23,000 rpm	
<b>Tube Dimensions Ø x L</b>	11 x 40 mm	
<b>Angle</b>	45°	
<b>K Factor</b>	199	
<b>Net Weight</b>	4.54 kg/10.0 lbs	
<b>Warranty</b>	15 years	
<b>Certifications</b>		
	<b>RCF</b>	<b>RADIUS</b>
<b>Maximum</b>	57,368 x g	97 mm
<b>Minimum</b>	37,851 x g	64 mm

## ROTOR AND ACCESSORIES ORDERING INFORMATION

		THERMO SCIENTIFIC	
		SORVALL LYNX 6000	SORVALL LYNX 4000
<b>Fiberlite F23-48x1.5</b>	Max. Speed	23,000 rpm	18,500 rpm
	Max. RCF	57,368 x g	37,116 x g

## Fiberlite F23-48x1.5 Rotor Package includes:

Description	Cat. No.
Fiberlite F23-48x1.5 Rotor	096-484075
Rotor Lid Assembly	099-484075
O-Ring Refresher Kit <sup>1</sup>	021-484075

## LABWARE ORDERING INFORMATION

Tube Vol. (mL)	Vol. Fill (mL)	Description	Cat. No.	Qty. /Pkg.	Tubes /Rotor	Max. Speed (rpm)	Max. RCF (x g)	Dims ØxL (mm)	REQUIRED TUBE CLOSURES, ADAPTERS, TOOLS & ACCESSORIES			
									Type	Cat. No.	Qty. /Pkg.	Description
1.5	1.5	Polyallomer Microtube	314352H01	100	48	23,000	77,427	11 x 40	Closure	Included	–	Snap-on Seal

 Biocontainment certification by the Public Health Laboratory Service, Microbiology Services, Porton Down, UK.

<sup>1</sup> Includes 5 O-Rings, 3 O-Ring Grease Packets and 4 oz FiberClene Lab Cleaner (017-0024).

© 2012 Thermo Fisher Scientific Inc. All rights reserved. All trademarks are the property of Thermo Fisher Scientific Inc. and its subsidiaries. Specifications, terms and pricing are subject to change. Not all products are available in all countries. Please consult your local sales representative for details.

For more information, please visit [www.thermoscientific.com/rotors](http://www.thermoscientific.com/rotors).

DSCFGLYNXF2348X15 1012

**Thermo**  
SCIENTIFIC  
Part of Thermo Fisher Scientific

SupplyLAB  
www.supplylab.pt